





2.MECHANICAL SPECIFICATIONS

ITEM	SPECIFICATIONS	ITEM	REMARK
Module Size(L×W×H)	107×85×11	mm	Reference Dimensional Outline
View Area(W×H)	88×60	mm	
Effective V/Area	83.15×54.35	mm	
Number of Characters	128×64	-	
Dot Pitch(W×H)	0.65×0.85	mm	
Dot Size(W×H)	0.6×0.8	mm	
Weight (Reflective/Led)	-	g	

3.ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	CONDITION	STANDARD	
			MIN	MAX
Logic Voltage	V _{DD}	Ta=25℃	-0.3V	7V
LCD Voltage	V _{LCD}		-0.3V	17.5V
Input Voltage	V _I		-0.3V	V _{DD} +0.3V
Operation Temperature	T _{OP}	—	-10℃	50℃
Storage Temperature	T _{St}	—	-20℃	60℃



5.LED BACKLIGHT SPECIFICATIONS

ITEM	SYMBOL	TYPE	MAX	UNIT
Ta=25℃				
Forward Voltage	V _f	80		V
Forward Current	I _f	—	—	mA
Emission Vave Length	λ _P	EL	—	nm

6.INTERFACE PIN CONNECTIONS

ITEM	SYMBOL	LEVEL	FUNCTIONS
1	VDD	+5V	Power Ground
2	VSS	0V	Power supply for logic
3	V0	—	Contrast adjust
4	RS	H/L	H:data L:command
5	R/W	H/L	H:read L:write
6	E	H.H→L	Enable signal
7-14	DB0-DB7	H/L	Data Bus
15	CSA	L	Chip selection signal A
16	CSB	L	Chip selection signal B
17	/RST	L	Reset signal
18	VOUT	—	Output voltage for LCD driving
19	BLA	+5V	Power supply for LED Backlight No Connection When Using EL Backlight
20	BLK	0V	
21	NC	—	No connection

7.ELECTRICAL CHARACTERISTICS

ITEM	SYMBOL	MIN	TYPE	MAX	UNIT
Ta=25℃					
Logic Power	V _{DD}	4.5	5	5.5	V
Input High Voltage	V _{IH}	0.8V _{DD}	—	V _{DD}	V
Input Low Voltage	V _{IL}	V _{SS}	—	0.8	V
Output High Voltage	V _{OH}	2.4	—	—	V
Output Low Voltage	V _{OL}	0	—	0.4	V
Logic Current	I _{DD}	—	6	8	mA
Operation Voltage For LCD	V _{DD} -V ₀	—	12.5	—	V